

SUCKER-ROD PUMP (SRP) DRIVE FEATURES

- Improves production, efficiency, and reliability
- Real-time multiple constraint optimization
- Pumping unit, rod string, and downhole pump models
- Tubing, casing, fluid, and reservoir models
- Automated system parameter identification
- Conventional, phased crank, beam balance, and air balance geometries
- Mark II, Reverse Mark, and Rotaflex geometries
- Rod string weight and resonance calculator
- Density and flow loss calculations from fluid and gas properties
- Deviated well compensation
- System simulation mode
- Manual, preset and remote speed control
- Pump speed and power flow optimizers
- Extend range operation to twice base speed
- Single-, dual-, or triple-speed operation
- Rotaflex racetrack mode with automatic cornering control
- Programmable crank angle speed-change set points
- Motor voltage, current, speed, and torque bar graph meters
- Gearbox torque monitor and limiter
- Counterbalance monitor and assistant
- Crank angle and speed monitors
- Operates without rod load and position sensors
- Optional load cell and inclinometer inputs
- Pump flow monitor and production accumulator
- Pump fill monitor and optimizer
- Dual speed pump-off control prevents sand-in problems
- Casing and tubing pressure compensation
- Pump intake and discharge pressure monitors
- Fluid level monitor and control
- Input power meter and energy efficiency monitor
- Input, motor, rod, and lift power monitors
- Peak and regen power limiters
- Power and torque smoothing control
- Motion profile optimizer to reduce gas interference
- Downhole pump position, velocity, and load monitors
- Rod position and velocity monitors
- Rod load monitor and limiter
- Rod/pump friction monitor
- Actual surface and pump dynamometer graph generators
- Predicted surface and pump dynamometer graph generators
- Stored surface and pump dynamometer graphs
- Bridle separation monitor and minimum rod load control
- Belt-slip monitor and diagnostic alarm
- Automatic restart from faults and power outages
- Time-stamped event, warning, and fault logging
- Standard ANSI and Modbus RTU serial communications
- Optional ControlNet, Modbus Plus, Profibus, and Ethernet
- Optional 900 MHz and 2.4 GHz wireless communications
- Optional interface for multichannel analog data logging
- Windows computer and Palm-type handheld interface software
- User-programmable Excel spreadsheet report generator software

All trade designations are provided without reference to the rights of their respective owners.



For more information on these products, please contact your local TS&M representative or email Production.Automation@dnow.com